



Eckdaten basic data (Sonderausführungen auf Anfrage)

Maximaldrehmoment <i>Maximum torque</i>	$M_{t_{max}}$ $M_{t_{max}}$	6000 Nm	Dauerwechsel Drehmoment <i>Alternating torque</i>	$M_{t_{dw}}$ $M_{t_{dw}}$	2900 Nm
Grenzdrehmoment <i>Limit torque</i>	$M_{t_{grenz}}$ $M_{t_{grenz}}$	10000 Nm	Drehzahl <i>Revolution</i>		1-3000 U/min (rpm)
Betriebstemperatur <i>Operational temperature</i>		-30°C - +120°C			
Rotationsdurchmesser <i>Diameter of rotation</i>		Ø 144 mm (D5)			
Rohrdurchmesser <i>Tube diameter</i>		Ø 100x3 mm (D7)			

GW	500-122	
L1	min. 515 mm	
LA	110 mm	

GW	513-122	
L1	360-459 mm	
LA	40-110 mm	

GW	505-122	
L1	min. 325 mm	

GW	507-122	506-122	
L1	235 mm mit with L2=72 mm	144 mm mit with L2=72 mm	



DIN Ø120/8-10	DIN Ø150/8-10 DIN Ø150/8-12	DIN Ø180/8-12 DIN Ø180/8-14 DIN Ø180/8-16
SAE Ø150/4-14.2		SAE Ø175/8-9.5 SAE Ø175/8-10
KV Ø120/4-11		KV Ø150/4-13